

The Fluido 2 microplate washer is ideal for both absorbance and luminescence based microplate assays. Ideal for busy laboratories running multiple microplate applications.

Biochrom[®] Anthos Fluido 2 Microplate Washer



Key Features

FLEXIBLE

- Up to 4 different channels and bottles allowing flexible configurations e.g. 3 wash and 1 rinse or 4 different wash solutions
- 8 and 12 channel manifolds supplied for 96 well plates. Optional 16-way manifold for 384 well plates.
- Easy plate setup and flexible software
- Automatic rinse to prevent clogging
- Wash without touching the well using automatic well depth detection and crosswise aspiration selectable functions
- Configurable to a range of microplate well types
- Three different rinse/prime methods

QUIET AND EFFICIENT

- Vacuum and pressure-free system with quiet pumps for a more peaceful lab.
- No warm-up time needed
- No special wash bottles required
- Efficient washing (< 1µL residual volume in flat bottomed plates)

EASY TO USE

- Color coded tube fittings
- Pre-programmed wash cycles and plate formats
- Manifold can be used to probe the parameters of the wells of the microplate

Program Options

- Up to 8 cycles can be included per procedure
- 20 different wash cycles can be defined including:
 - Bottom and overflow washing options
 - Adjustable dispense volume and speed
 - Adjustable aspiration speed and time
 - Adjustable soak time
 - Shaking (3 modes)
- Fifty different procedures may be created by putting up to 8 previously defined wash cycles in sequence
- Washing procedures can either be over the whole plate or a few strips.
- Overflow and bottom washing options

Safety Features

- Manifold cover reduces aerosols
- Emergency stop (prevents damage to the microplate)
- Optional liquid level warnings and liquid level sensors

TECHNICAL DETAILS

Biochrom Anthos Fluido 2 Microplate Washer

Dispensed volumes	50 - 2000µL in 50µL increments (for 8 and 12-way manifolds) 50 - 500µL in 25µL increments (for 16-way manifold)
Dispensing precision	< 5% at 300µL across the plate (for 8 and 12-way manifolds) < 5% at 100µL across the plate (for 16-way manifold)
Residual volume	<1µL per well
User interface	2 x 16 characters backlit display Keyboard with 5 function keys
Shaking	3 speed
Microplates	96 well plates flat and round bottomed (384 well plates with 16-way manifold)
Power requirement	90 -130V, 180 -250 VAC (autosensing), 47/66Hz
Languages	English, German
Instrument dimensions (wxhxd)	28 cm x 22 cm x 42 cm (11" x 8.7" x 16.5")
Weight:	6.2 Kg (13.7lbs)

ORDERING INFORMATION:

80-4000-10	Biochrom Anthos Fluido 2 96 W2 Microplate Washer for 96 well Plates 2 liquid lines, 8 and 12-way manifolds and tubing, 1 wash bottles (2L), 1 rinse bottle (2L), 1 waste bottle (2.5L)
80-4000-11	Biochrom Anthos Fluido 2 96 W4 Microplate Washer for 96 well Plates 4 liquid lines, 8 and 12-way manifolds and tubing, 3 wash bottles (2L), 1 rinse bottle (2L), 1 waste bottle (2.5L)
80-4000-12	Biochrom Anthos Fluido 2 384 W2 Microplate Washer for 96 and 384 well Plates 2 liquid lines, 8 and 16-way manifolds and tubing, 1 wash bottles (2L), 1 rinse bottle (2L), 1 waste bottle (2.5L)
80-4000-13	Biochrom Anthos Fluido 2 384 W4 Microplate Washer for 96 and 384 well Plates 4 liquid lines, 8 and 16-way manifolds and tubing, 3 wash bottles (2L), 1 rinse bottle (2L), 1 waste bottle (2.5L)

All Fluido 2 Microplate washers come with cleaning tools for manifold needles, spare fuses, power cable and user manual.

Distributors Worldwide



Biochrom Ltd
Tel: +44 1223 423723
Fax: +44 1223 420164
Email: enquiries@biochrom.co.uk
www.biochrom.co.uk

Biochrom US
Tel: 877- BIO-CHROM (877-246-2476) (Toll free)
Tel: 508-893-8999
Fax: 508-429-5732
Email: sales@biochrom-us.com
www.biochrom-US.com